

APACHE 4 PRO

MULTI-PURPOSE SURVEY USV



► Highlights

The APACHE 4 Pro is a versatile Unmanned Surface Vessel (USV) designed to meet a wide range of hydrological survey needs. It is compatible with a variety of mainstream Acoustic Doppler Current Profilers (ADCPs) and integrates seamlessly with the CHCNAV HQ-400 Multibeam Echo Sounder (MBES) for detailed underwater bathymetric surveys.



► Protection for Every Mission



Lighter and Stronger
Materials



Smart Tangle
Prevention



Precision Depth
Measurement



Multi-Function Capability:
Depth and Flow


► Strong and collision-resistant hull

30% ↘

Hull weight reduced by 30%

60% ↗


10 MPa Strength:
60% better impact resistance



High-strength

High-modulus materials
One-piece molded hull construction High-density
Small-aperture mesh cover

► Hybrid Water Pressure Conversion Technology & Real-time Tangle Self-Check Technology



Engineered dynamics for 70% lower entanglement in
challenging environments



Proactive tangle alarm for long-lasting motor

► Multiple Uses and Compatibility with Various Equipment



Optional multibeam echo sounder and automatic SVP launching kits.

Adaptive water flow straight-line technology, compatible with mainstream ADCP for a wide range of measurement scenarios.

► Adaptive measurement ensures precise data capture in complex environments.



Highly sensitive, anti-interference transducers with adaptive parameter tuning for complex survey scenarios.



3 mm ranging resolution



10 cm blind zone



+6 dB SNR improvement

► EasySail: All-in-one Android software for bathymetric and hydrological surveys



No additional computer required for efficient operation

Integrated multibeam display, control, and acquisition system, with scan data overlaid on satellite imagery. Automatic parameters adjustment for ensuring optimal coverage.



Enhanced hydrology functions

Supports satellite map overlay with flow velocity vector diagrams, data playback and post-processing, and one-click data synchronization.

► Use Cases



Water Resource Survey



Hydrological Survey



Channel Dredging



Emergency Rescue

SPECIFICATIONS

► Physical

Hull Dimension (L x W x H)	1280 mm x 720 mm x 420 mm
Material	High strength, high modulus carbon fiber
Process	HPT one-piece molding
Weight (w/o battery and antenna)	29.6 kg
Maximum Payload	50 kg
Anti-Wave & Wind	3 rd wind level and 2 nd wave level
Hull Design	M-type triple-hull
GNSS	Internal GNSS dual antenna
Waterproof	IP67
Quick Transport	Removable land-assist transport wheels
Draft	8.6 cm (unladen)
Indicator Light	Two-color (positioning and differential signal)
Camera	360° omnidirectional video
ADCP Mounting Hole	240 mm
ADCP Compatibility	Compatible with RiverStar, M9, RiverPro, RiverRay, RioGrande and other ADCP
Available Instrumentation	ADCP, integrated compact multibeam echosounder, side scan sonar, water quality monitor, sampling bucket
Obstacle Avoidance Distance & Range	0.2–40 m (H: 112°, V: 14°)

► Propulsion

Propeller Type	Brushless DC
Direction Control	Veering without steering engine
Rated Motor Power	1000 W
Maximum Motor Speed	7200 ± 5% RPM
Motor Installation	Pluggable
Li-ion Battery Capacity	32.4 V, 23.1 Ah
Battery Endurance	10 h @1.5 m/s (1 battery set, expandable)
Power Supply	Single/dual balanced battery support
Battery Replacement	Hot swap supported
Charging Time	3 h
Maximum Speed	6.5 m/s

► Remote Control

Dimension (L x W x H)	350 mm x 195 mm x 101 mm
Display Screen	10-inch
Resolution Ratio	1920 x 1200
Internal Storage	RAM: 4 GB, Storage: 64 GB
Battery Endurance	5 h
Communication Frequency	2.4 GHz
Peripheral Interface	USB, Nano SIM, TF card (up to 128 GB), Type-C

► Communications

Data Communication	Standard 4G and Remote control
Remote Control Range	1.5 km (Remote) ⁽¹⁾ ; Unlimited (4G)
SIM Card Slot	Nano SIM
Reserved Interface	2x RJ45 ports, 2x RS232 serial ports
Navigation Mode	Manual or Auto-Pilot
Data Storage	Local (multi-channel) & Remote

CHC Navigation Headquarter

577 Songying Road, Qingpu,
201703, Shanghai, China
Marketing@chcnv.com
+86 21 54260273

CHC Navigation Europe Kft

Office Campus, Building A, 6/B Gubacsi Street,
Budapest 1097, Hungary
Europe_office@chcnv.com
+36 20 510 6723

► Software

	Route planning and autonomous navigation. Total mileage statistics, remaining mileage reminder, multi-angle video and online map display. Hull parameter control, physical & virtual joysticks, system self-check at power-on. Waveform overlay and attitude correction. Coordinate conversion, trajectory, water depth, waveform and hull parameter real-time display. Online software/firmware updates. Export via USB/Type-C. Single beam mode: Data collection and post-processing. Hydrological mode: Flow test results output. Multibeam mode: Real-time parameter adjustment.
EasySail	

► Positioning

Satellite System	BDS B1I/B2I/B3I, GPS L1C/A/L2C/L5, Galileo E1/E5a/E5b, GLONASS L1/L2, QZSS L1/L2/L5
Single Point Position (RMS)	Horizontal: 1.5 m Vertical: 2.5 m
DGNSS Positioning Accuracy	Horizontal: ±(0.4 m + 1 ppm) Vertical: ±(0.8 m + 1 ppm)
RTK Positioning Accuracy	Horizontal: ±(8 mm + 1 ppm) Vertical: ±(15 mm + 1 ppm)
Radio Protocols	Satel 3AS, CHC ⁽²⁾ , TT450, Transparent
Heading Accuracy	0.1 ° @ 1 m baseline
Inertial Navigation Stability	6 °/h (accuracy attenuation 1 m after 20 s)
IMU Update Rate	200 Hz

► D270 Single Beam Echo Sounder

Data Type	CHCGD ⁽²⁾ , NMEA SDDPT/SDDBT, original waveform
Sounding Range	0.1 m to 200 m
Sounding Accuracy	±0.01 m + 0.1% x D (D is the depth of water)
Resolution	3 mm
Maximum Sampling Rate	30 Hz
Frequency	200 kHz
Beam Angle	5°
Sound Velocity Adjustment Range	1400–1700 m/s
Integrated Water Temperature Sensor	-55°C~+100°C, real-time correction of the sound speed

*Specifications are subject to change without notice.

(1) For best communication, keep the remote controller at least 1.5 m above water level. Actual range may be affected by weather, swells, electromagnetic interference, and other environmental conditions.

(2) CHCGD & CHC protocol is CHCNAV format.

© 2026 Shanghai Huace Navigation Technology Ltd. All rights reserved. The CHC and CHC logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners. Revision August 2026.

